

Printing date 10/04/2018

Reviewed on 10/04/2018

1 Identification

- **Product identifier**
- **Trade name:** Isobutyl Alcohol, ACS Grade
- **Article number:** 300125
- **CAS Number:**
78-83-1
- **EC number:**
201-148-0
- **Molecular Formula** C₄ H₁₀ O
- **Molecular Weight** 74.12
- **Application of the substance / the mixture** For Research Use Only
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MP Biomedicals, LLC
29525 Fountain Parkway
Solon, OH 44139
United States
www.mpbio.com
- **Information department:** Quality Control Department
- **Emergency telephone number:** CHEMTREC: 1-800-424-9300 (1-703-527-3887)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS05



GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Isobutyl alcohol

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 1)

· **Hazard statements**

- Flammable liquid and vapor.
- Causes skin irritation.
- Causes serious eye damage.
- May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Wash thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a poison center/doctor.
- Specific treatment (see on this label).
- Take off contaminated clothing and wash it before reuse.
- If skin irritation occurs: Get medical advice/attention.
- In case of fire: Use for extinction: CO₂, powder or water spray.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
78-83-1 Isobutyl alcohol

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 2)

- **Identification number(s)**
- **EC number: 201-148-0**

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Consult your Doctor. Show the safety data sheet to the Doctor. Away from the dangerous area.
- **After inhalation:** If breathed in, supply fresh air. If not breathing, give artificial respiration. Consult a Doctor.
- **After skin contact:** Wash off with soap and plenty of water. Consult a Doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Pick up mechanically, dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:	
	150 ppm
· PAC-2:	
	1,300 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 3)

· **PAC-3:**

8000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace. Avoid direct contact with skin and eyes.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** 15-30°C
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Further information about storage conditions:**
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see Section 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

78-83-1 Isobutyl alcohol

PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Long-term value: 150 mg/m ³ , 50 ppm
TLV	Long-term value: 152 mg/m ³ , 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 4)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Indeterminate
Odor threshold:	Not determined.

- **pH-value:** 7

- **Change in condition**

Boiling point/Boiling range: Undetermined.

- **Flash point:** 28 °C (82.4 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 427 °C (800.6 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	1.7 Vol %
Upper:	12 Vol %

- **Vapor pressure:** Not Applicable

Density:	Not Applicable
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

- **Solubility in / Miscibility with** Not Determined

- **Water:** Not determined.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 5)

Organic solvents:	100.0 %
VOC content:	100.00 %
	1,000.0 g/l / 8.35 lb/gal
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Dermal	LD50	3,400 mg/kg (rabbit)
--------	------	----------------------

78-83-1 Isobutyl alcohol

Oral	LD50	2,460 mg/kg (rat)
------	------	-------------------

Dermal	LD50	3,400 mg/kg (rabbit)
--------	------	----------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

Substance is not listed.

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

ATE (Acute Toxicity Estimate)

Oral	LC50 / 96 h	1,220 mg/L (Pimephales promelas)
------	-------------	----------------------------------

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 6)

78-83-1 Isobutyl alcohol

Oral LC50 / 96 h 1,220 mg/L (*Pimephales promelas*)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Assessment by list): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Can not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Discard must be made according to official regulations.*

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1212
- **UN proper shipping name**
- **DOT** *Isobutanol*
- **ADR** *1212 Isobutanol*
- **IMDG, IATA** *ISOBUTANOL (ISOBUTYL ALCOHOL)*

- **Transport hazard class(es)**

- **DOT**



- **Class** *3 Flammable liquids*
- **Label** *3*

- **ADR, IMDG, IATA**



- **Class** *3 Flammable liquids*
- **Label** *3*

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 7)

· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids 30 F-E,S-D A
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations · Hazardous substance:	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L 3838 lbs, 28982 kg
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1212 ISOBUTANOL, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is not listed.

· **TSCA (Toxic Substances Control Act):**

Substance is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 8)

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

Substance is not listed.

· **TLV (Threshold Limit Value established by ACGIH)**

Substance is not listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Isobutyl alcohol

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/04/2018

Reviewed on 10/04/2018

Trade name: Isobutyl Alcohol, ACS Grade

(Contd. of page 9)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Quality Control Dept.

· **Date of preparation / last revision** 10/04/2018 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3